
Los Angeles Series Short Pendant






Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting	Louver
• W 13 • HT 8 • OAH 48 (OverAll Height)	GGQ	5,400lm LED (33W)	1	PC	WA	ST CH SM SP	SQ
	АНМ	3-100W A21 (300W)	1	PC	WA	ST CH SM	SQ

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options



PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic cylinder diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin contact us for alternate color temperature availability

Abbreviation Key

Lamps

100W A21 Medium Base, 100W Max, Incandesent or LED

Finish Types

PC Powder Coat

Diffuser Types

WA Standard Acrylic Diffuser

Mountings

ST Stem
CH Chain

SM Surface Mount Chain

D1

SP Steep Pitch Canopy for Stem

Louvers

SQ Square Cell

Dimming Types

1

D2

- Standard LED CRI is 80 contact us for alternate CRI availability
 Incandescent lamping is Triac or ELV dimmable consult lamp and dimmer manufacturer for compatibility.
 Standard LED dimming is 0-10v
 Optional line voltage (Triac or ELV) LED dimming is available consult for compatibility
 Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH Over All Height is the length from the ceiling to the bottom of the fixture.)
 Mounts to standard electrical junction box (by others), Box may require additional structural support (by others)
 For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- (Stem only)

 UL / cUL or ETL / cETL listed

 Contact Us for more lamping options.